















UMTS | HSDPA 7.2

UC864-E Compact



-  Ultra Compact
-  Telit Unified AT Command Set
-  Telit Unified Form Factor
-  Multi Band
-  Single Band UMS | HSDPA 7.2
-  Quad Band Edge
-  Quad Band GPRS
-  RoHS Compliant
-  80 Pin Connector
-  USB 2.0 Full Speed Compatible
-  Extended Temperature Range
-  Extended RF Sensitivity
-  Embedded TCP/IP Stack



TELIT INFINITA SERVICES



The UC864-E is a 3.5G wireless data module designed to be fully compatible with Telit's GSM/GPRS and CDMA products in the compact, unified form factor family. This enables integrators and developers to design their applications once and take advantage of the truly global coverage and service flexibility afforded by the combination of the two most prevalent cellular technologies worldwide.

Designed to minimize costs of applications local to the European market, the UC864-E features a single-band 2100MHz UMS/HSDPA radio. For applications requiring global portability, the UC864-G tri-band variant is also available.

With its ultra-compact design, and extended operating temperature range, the Telit UC864-E is the perfect platform for medium-to-high-volume m2m applications and mobile data and computing devices. Additional features such as, integrated TCP/IP and UDP, and a three channel ADC provide extended functionality, adding value to the end application without adding cost.

The UC864-E is also fully backward compatible to existing EDGE and GSM/GPRS networks through accomplished quad-band radios. The extensive interface set, which includes IIC and user definable GPIO, provides ease of integration of peripherals and actuators.

As part of Telit's commitment to protecting the customer investment in developing and deploying Telit based solutions, UC864-E supports Over-the-Air firmware update by means Premium FOTA Management. By embedding RedBend's vCurrent® agent, a proven and battle-tested technology powering hundreds of millions of cellular handsets world-wide Telit is able to update its products by transmitting only a delta file, which represents the difference between one firmware version and another.


As a part of Telit's corporate policy of environmental protection, all Telit products comply to the RoHS (Restriction of Hazardous Substances) directive of the European Union (EU Directive 2002/95/EG).

Product features

- HSDPA 7.2 Mbps
- UMS/HSDPA (WCDMA/FDD) 2100 MHz
- Quad-band EGSM 850 / 900 / 1800 / 1900
- GPRS multi-slot class 12
- EDGE multi-slot class 12
- Dimension: 30 x 36.2 x 4.8 mm
- Weight: 10 grams
- Extended temperature range -30°C to +80°C (operational) -40°C to +85°C (storage temperature)

UC864-E

Compact



actual size

Interfaces

- 80-pin Molex connector
- 1.8/3V UICC SIM card interface
- 22 GPIOs, 3 A/D and 1 D/A converter
- USB 2.0 full speed interface
- 50 Ohm murata GSC antenna connector
- ITU-T V.24 serial link through CMOS UART, PCM interface
- Buzzer output

Approvals

- CE, GCF

Data

- HSDPA
 - Downlink up to 7.2 Mbps
 - Uplink up to 384 kbps
- WCDMA
 - Downlink/uplink up to 384 kbps
- EDGE
 - Downlink up to 236.8 kbps
 - Uplink up to 118 kbps
- GPRS
 - Downlink up to 85.6 kbps
 - Uplink up to 42.8 kbps
 - PBCCH support
- CSD
 - Downlink/uplink up to 14.4 kbps
- Available modes of operation
 - AT commands on UART & data on USB
 - AT commands on USB & data on UART

Electrical

- Output power
 - Class 4 [2 W, 33 dBm] @ GSM850 / 900
 - Class 1 [1 W, 30 dBm] @ GSM 1800 / 1900
 - Class 3 [0.25 W, 24 dBm] @ UMTS
 - Class E2 [0.5 W, 27 dBm] @ EDGE850/900
 - Class E2 [0.4 W, 26 dBm] @ EDGE1800/1900
- Sensitivity
 - -108.2 dBm @ WCDMA 2100 MHz
 - -107 dBm @ GSM 850 / 900 MHz
 - -106 dBm @ DCS1800 / PCS1900 MHz
- Supply voltage
 - Nominal: 3.8 VDC
 - Range: 3.4 - 4.2 VDC
- Power consumption
 - Off: < 26 μ A
 - Idle @ mode GSM: < 3.3 mA
 - Idle @ mode UMTS: < 4.1 mA
 - WCDMA voice channel < 690 mA @ worst network conditions
 - GSM voice channel < 317 mA @ worst network conditions
 - WCDMA data channel < 680 mA @ worst network conditions
 - HSDPA channel < 730 mA @ worst network conditions
 - GPRS Class 12 < 790 mA @ worst network conditions
 - EGPRS Class 12 < 560 mA @ worst network conditions

Additional features

- Voice and SMS
- TCP stack with IP and UDP protocols
- Standard and extended AT command set
- Minimal power consumption
- PFM (Premium FOTA Management) Over the Air Update
- MUX driver for WinCE
- RIL Driver for WinCE
- USB Driver for WinCE, WinXP/Vista/W7, Linux and QNX.

Order-No.

Please contact your Telit representative for order codes and all further information

Copyright © 2010, Telit
Subject to changes in technology, design and availability

Distributed by:

Telit wireless solutions

Telit Communications S.p.A.
Via Stazione di Prosecco, 5/B
I-34010 Sgonico (Trieste), Italy
Tel +39 040 4192 200
Fax +39 040 4192 289
E-Mail: EMEA@telit.com
www.telit.com

Telit Wireless Solutions Inc.
3131 RDU Center Drive, Suite 135
Morrisville, NC 27560, USA
Tel +1 888 846 9773 or +1 919 439 7977
Fax +1 888 846 9774 or +1 919 840 0337
E-Mail: NORTHAMERICA@telit.com
www.telit.com

Telit Wireless Solutions Inc.
Rua Cunha Gago, 700 - cj 81, Pinheiros
São Paulo - SP, 05421001, Brazil
Tel +55 11 2679 4654
Fax +55 11 2679 4654
E-Mail: LATINAMERICA@telit.com
www.telit.com

Telit Wireless Solutions Co., Ltd.
9th FL, Daewoo Securities Bld.
34-3 Yeouido-dong, Yeongdeungpo-gu
Seoul 150-716, KOREA
Tel +82 2 368 4600
Fax +82 2 368 4606
E-Mail: APAC@telit.com
www.telit.com